



17" CRT DISPLAY
E72f⁺sb



High Brightness 500nits

UltraBrite™
Hot Key



OSD Lock Function

0.21mm
Ultra-fine
Dot Pitch



SuperClear® technology



➤ Let You See The Authenticity World !



High range capability, mid range affordability-E72f⁺sb 17" Display

ViewSonic's sleekly engineered bandbox monitor – E72f⁺sb lets you look brighter and better than ever. A press of the UltraBrite™ Hot Key gives you full control of 500 nits of brightness, preset in 3 convenient modes. Our SuperClear® technology uses an enhanced phosphor treatment and optimized glass filter, giving you vivid colors and image clarity. The OSD power lock function keeps your settings the way you want them. The stylish silver-on-black E72f⁺sb CRT is built with all the features you expect to enhance your productivity as well as your visual experience.

All the wonderful functionality and features you expect from ViewSonic, for less than you expect!

UltraBrite™ Technology

New UltraBrite™ CRT enables optimized viewing of video and graphic applications. Games, TV and DVDs come alive with rich saturated color and vivid contrast. Precise definition and photo-realistic image quality boost 3-D video and professional graphic performance.

- 0.21mm Horizontal Dot Pitch
- 0.25mm Diagonal Dot Pitch
- 1280 x 1024 Maximum Resolution

Displays a maximum resolution of 1280 x 1024 at 67Hz flicker-free refresh rate for easy-on-the-eyes viewing.

1280 x 1024 @ 67Hz
1024 x 768 @ 90Hz
832 x 624 @ 108Hz
800 x 600 @ 112Hz
640 x 480 @ 138Hz

- OnView® controls including ViewMatch® Technology

Screen adjustments are made via the OnView menu using simple on-screen controls. ViewMatch feature allows easy adjustment to color temperature and intensity for optimal screen-to-print color matching.

- Anti-static, Anti-reflective Screen

This specially formulated anti-glare, anti-reflection screen treatment uses a multi-layer process to eliminate reflection while maintaining the highest image quality.

- SuperClear® Technology

SuperClear® screen technology incorporates enhanced phosphor treatment and optimized glass filter to deliver vivid colors and image clarity.

- PerfectFlat® Screen

Absolutely flat screen provides realistically proportioned, precise images with reduced reflection, image distortion and eye fatigue.

- MPRII and Energy Star Certified

- PC and Mac® Compatible

- Best Service & Support

At ViewSonic, we are devoted to customer satisfaction. We strive constantly to understand your interests and concerns, and treat you with respect, courtesy and consideration. For warranty information, please contact your local ViewSonic distributor or ViewSonic service center.

ViewSonic Service Center :

Taiwan - service@tw.viewsonic.com

China - service.cn@cn.viewsonic.com

Japan - service.jp@jp.viewsonic.com

Korea - service.kr@kr.viewsonic.com

Hong Kong - service@hk.viewsonic.com

S. Asia & S. E. Asia - service@sg.viewsonic.com

Australia & New Zealand - service@au.viewsonic.com

S. Africa & other countries - service@sd.viewsonic.com



E72f+sb

17" CRT Display

Model No : VS10083

CRT	Type	17" (16.0" viewable)
	Brightness	500nits
	Dot Pitch	0.21mm horizontal, 0.13mm vertical, 0.25mm diagonal
	Glass Surface	Anti-reflection, anti-glare, anti-static
INPUT SIGNAL	Video	RGB analog (75 ohms, 0.7/1.0 Vp-p)
	Sync	H/V separated (TTL), composite
	Frequency	Fh: 30~72kHz; Fv: 50~160Hz
COMPATIBILITY	PC	from VGA up to 1280 x 1024
	Mac®	Power Mac® up to 1280 x 1024
CONNECTOR	Signal	15-pin mini D-sub
	Power	3-pin plug (IEC320)
POWER	Voltage	AC 90-264VAC (auto switch) 50/60(+/-3) Hz
	Consumption	75W (typ)
CONTROLS	Basic	Power On/Off, 1, Down, Up, 2, UltraBrite™ HotKey
	OnView®	Brightness, Degauss, Contrast, H/V Size, H/V Position, Pincushion, Pinbalance, Trapezoid, Parallelogram, Tilt, Moiré Reduction, View Meter®, ViewMatch® (9300, 6500, User), Language, OSD Position, Zoom, and Memory Recall
VIDEO INPUT	Bandwidth	110MHz
MISCONVERGENCE		0.25mm (max) at center 0.35mm (max) at corner
DISPLAY AREA	Factory Setting	310mm (H) x 230mm (V)
	Maximum Scan	325mm (H) x 243mm (V) (dependent upon signal timing used)
OPERATING CONDITIONS	Temperature	0-40° C (32-104° F)
	Humidity	5-95% (non-condensing)
DIMENSIONS (WxHxD)	Physical	408.8mm x 432.6mm x 385.1mm 16.1" x 17.1" x 15.2"
WEIGHT	Net	16.2 kg (35.7lbs)
	Gross	18.1 kg (39.9lbs)
REGULATIONS		UL, cUL, FCC-B, ICES-003, CB, DHHS, MPRII, EPA-Energy Star®, ISO9241-378, CE, CCC, NOM, TUV/GS, TUV/Ergo, Gost-R, SASO, PCBC, BSMI, PSB, C-Tick, Argentina-TUV/S, TCO'99(for VSE)
POWER MANAGEMENT		Meets MPRII standards

Specifications subject to change without notice.

Selection, offers, warranties and programs may vary by country; see your ViewSonic representative for complete details.

Headquarters :

381 Brea Canyon Road,
Walnut, CA 97189, U.S.A.
Tel:(800)888-8583 (909)444-8888
Fax:(909)839-7922
E-mail:salesinfo@viewsonic.com
www.viewsonic.com

Asia Pacific :

9F, No. 192 Lien Chien Road,
Chung Ho, Taipei, R.O.C.
Tel:886-2-2246-3456
Fax:886-2-8242-3666
www.viewsonic.com.tw

www.viewsonic.com