


LCD DISPLAY  
**VA1912w**



sRGB Color  
Management



High-definition,  
wide-screen LCD.



### ViewSonic VA1912w - 19" wide-screen LCD Display

The ViewSonic VA1912wb 19" LCD will impress you with its generous feature set and its budget friendly price. The 16:10 WIDE-SCREEN ASPECT RATIO PROVIDES MORE PRODUCTIVE SPACE for multiple windows, HD-format video and immersive gaming action. ViewSonic's innovative Dynamic Structure™ technology ACCELERATES VIDEO RESPONSE FOR BROADCAST-QUALITY, seamless video. The ClearMotiv™ fast 8ms video response, 300 nits of brightness (typ), 500:1 contrast ratio (typ), and 1440x900 optimum resolution deliver crystal-clear images, crisp text and intense graphics. OSD lock and AutoTune® functions ensure your view is always optimal. Furnish your workplace in style with the feature-rich, wall-mountable, value-priced VA1912wb.

## 16:10 Wide-screen experience

16:10 wide-format screen is ideally suited to maximize natural field of vision for intense game play, HD format video, and multiple document windows.

### ClearMotiv™ technology

Human vision allows images shown at 24 frames per second (fps) to be perceived as smooth motion video. Movies play at 24fps, analog TV at 30fps, and DTV ranges between 24-60 fps depending on HDTV format. ClearMotiv™ fast video-response technology allows frame rates up to 125fps for true broadcast quality full-motion video.

### Ultra-Slim Bezel

The ultra-slim bezel makes more productive use of the screen area while minimizing the image gap in multidisplay applications for continuous data display which enhances the visual experience with clean, minimalist borders around the active image area.

### OptiSync™ Technology

This multi-mode input technology supports both analog video (VGA) and direct-digital input (DVI) for superior image quality. The digital interface delivers optimized image quality with minimum adjustment for ultimate configuration flexibility.

### sRGB Color Management

The sRGB color management chip technology ensures color accuracy from screen to print when used with other sRGB-compliant peripherals.

### OnView® controls Including ViewMatch Technology

Screen adjustments are made via an on-screen menu using simple controls. This user-friendly control system easily adjusts image quality, size, position and geometry for optimal viewing.

### AutoTune™ Function

Provides the best image by monitoring signals from the computer and automatically optimizing the monitor settings.

### OSD/Power Lock Function

When activated, the user-controlled OSD/Power lock function prevents changes to monitor settings, maintaining an optimized image.

### Best Service & Support

At ViewSonic, we are devoted to customer satisfaction. We strive constantly to understand your interests and concerns, and treat you with respect, courtesy and consideration. For the warranty information, please contact your local ViewSonic distributor or ViewSonic service center.

### ViewSonic Service Center

Taiwan - service@tw.viewsonic.com  
China - service.cn@cn.viewsonic.com  
Australia & New Zealand - service@au.viewsonic.com  
Japan - service@jp.viewsonic.com  
Hong Kong service@hk.viewsonic.com  
Korea service@kr.viewsonic.com  
Singapore/Malaysia/Thailand service@sg.viewsonic.com  
Other AP countries/South Africa service@sd.viewsonic.com

**Headquarters:**  
381 Brea Canyon Road,  
Walnut, CA 97189, U.S.A.  
Tel(800)888-8583 (909)444-8888  
Fax(909)839-7922  
www.viewsonic.com

**Asia Pacific:**  
9F, No. 192 Lien Chien Road,  
Chung Ho, Taipei, R.O.C.  
Tel886-2-2246-3456  
Fax:886-2-8242-3666  
www.viewsonic.com.tw

**ViewSonic Hong Kong**  
Suite 811, East Wing, Tsimshatsui Centre,  
66 Mody Road, TST East  
Kowloon, Hong Kong  
Tel2268-6878  
Fax:2268-6778  
www.hk.viewsonic.com

**ViewSonic (Singapore) Pte Ltd**  
221 Henderson Road #04-08  
Henderson Building  
Singapore 159557  
Tel+65-6273-4018  
Fax:+65-6273-1566  
www.viewsonic.com.sg

**ViewSonic Australia Pty Ltd**  
Unit 3, 44 Dickson Avenue,  
Artarmon NSW 2064,  
Australia  
Tel(02)9906-6277  
Fax(02)9906-6377  
www.viewsonic.com.au



## VA1912w 19" LCD Display

Model No:VS10866

LCD	Display Area	19.0" diagonal
	Optimum Resolution	1440 × 900
	Brightness	300 nits (Typ.)
	Contrast Ratio	500:1 (Typ.)
	Viewing Angle	130° (Horizontal), 150° (Vertical)
	Response Time	8ms
	Pixel Pitch	0.285mm(H) x 0.285mm(V)
	Panel Surface	Anti-glare
INPUT	Analog	RGB Analog
	Digital	DVI-D
	Sync	H/V Separated
	Frequency	FH : 30-82kHz, Fv : 50-85Hz
COMPATIBILITY	PC	VGA up to 1440 × 900 Non Interlaced
	Mac	Power Mac, up to 1440 × 900
CONNECTOR	Analog	15 pin mini D-sub × 1
	Digital	DVI-D
	Audio-in	15 pin mini D-sub x1
	Power	Built-in power Adapter, 3-Pin plug
AUDIO	Speaker	1Wx2
POWER	Voltage	100-240VAC; 50/60 Hz (Switch)
	Consumption	70.5W (Max.) 60W (Typ.)
CONTROLS	Basic	Mute [1], [Down], [Up], [2], power button
	OnView	Auto Image Adjust Contrast/Brightness Input Select Analog / Digital Audio Adjust Volume, Mute Color Adjust sRGB, 9300K, 6500K(default), 5400, 5000, User Color [R, G, B] Information H Frequency, V Frequency, Resolution, Pixel Clock, Serial Number, Model Number, www.ViewSonic.com Manual Image Adjust H. Size, H./V. Position, Fine Tune, Sharpness Setup Menu Language (English, French, German, Spanish, Italian, Finnish, Japanese, Traditional Chinese, Simplified Chinese), Resolution Notice, OSD Position, OSD Timeout, OSD Background Memory Recall
OPERATING CONDITIONS	Temperature	0° C - 40° C
	Humidity	10% - 90% (Non condensed)
DIMENSIONS (W×H×D)	Physical	451mm × 391mm × 197mm
WEIGHT	Net	4.5 kgs
REGULATIONS		CB / TCO99 / UL/cUL / FCC-B / ICES 003 / Argentina- TUV/S / NOM / EPA Energy Star / TUV/Ergo / ISO134062 / TUV/GS / CE / GOST-R / SASO / BSMI / PSB / C-Tick / Korea (MIC) / CCC
POWER MANAGEMENT		Meet TCO99, Energy Star standards

Specifications subject to change without notice.

