



DOM E CAMERA

FEATURES

- Low light sensitivity is achieved by using advanced 1/3" Sony colour CCD
- Electronic shutter and AGC allows the camera to be used in environment with varying light levels
- System available in PAL

Model No.	ZCCDBRU
Image Sensor	1/3" SONY CCD
Horizontal Resolution	420 TVL
Min Illumination	0.5 Lux / F1.2
Power Source	12V DC
Lens	3.6mm Board Lens
Iris	Fixed
Operating Temperature	0° to 50° C, 20 ~ 80%
Auto Gain Control	Auto
White Balance	Auto
Backlight Compensation	Auto
S / N Ratio	≥ 48 dB



IR DOM E CAMERA

FEATURES

- Advanced 1/3" Colour CCD
- High - resolution with 480 TVL
- 22 IR LED having 1,00,000 hrs of lifespan
- Electronic shutter and AGC allows the camera to be used in environment with varying light levels
- Versatile and adjustable for desired veiwing range

Model No.	ZCCIVAB	ZCCIVAC	ZCCIBRT	ZCCICRT
Image Sensor	1/3" SONY CCD	1/3" SONY CCD	1/3" SONY CCD	1/3" SONY CCD
Horizontal Resolution	420 TVL	480 TVL	420 TVL	480 TVL
Min Illumination	0 Lux / F1.2	0 Lux / F1.2	0 Lux / F1.2(LED ON)	
IR LED	36 units	36 units	22 units	22 units
Power Source	12V DC	12V DC	12V DC	12V DC
Auto Gain Control	Auto	Auto	Auto	Auto
White Balance	Auto	Auto	Auto	Auto
Backlight Compensation	Auto		Auto	Auto
S / N Ratio	≥ 48 dB	≥ 48 dB	≥ 48 dB	≥ 48 dB
IR Range	20 Mtr	20 Mtr	20 Mtr	20 Mtr
Lens	3.8 - 8 mm	3.8 - 8 mm	4 mm Fixed	4 mm Fixed
Operating Temperature	0° to 50° C, 20 ~ 80%		0° to 50° C, 20 ~ 80%	
Weather Proof Rating	IP66	IP66	-	-